

BOROUGH OF ORWIGSBURG

Schuylkill County, Pennsylvania

ORDINANCE NO. 212

AN ORDINANCE AMENDING ORDINANCE NO. 191  
OF THE BOROUGH OF ORWIGSBURG RELATING  
TO THE MANNER OF CONSTRUCTION OF CURBS  
AND FIXING THE MINIMUM REQUIREMENTS  
THEREOF.

\*\*\*\*\*

BE IT ENACTED and ORDAINED by the Borough Council of the Borough of Orwigsburg, in council duly assembled, and it is hereby enacted and ordained by authority of the same, as follows:

Section 1. That Section 2 of Ordinance No. 191 of the Borough of Orwigsburg, ordained and enacted May 14, 1969, is hereby amended so that the same shall read as follows:

(a).....Curb Machine. Plain cement concrete curb may be placed with a self-propelled machine consisting of a hopper, power-driven screw or screws and a metering device.

Concrete shall be uniformly fed to the machine and after extrusion, the concrete will maintain the shape of the section without slumping.

The finished curb shall have a surface free from voids and honeycomb. Any additional surface finishing required shall be performed immediately after extrusion.

Method of Measurement-This work will be measured by the linear foot, surface measurement along the face of the curb, and will include depressed curb.

Basis Of Payment-Plain cement concrete curb will be paid for at the contract unit price per linear foot, complete in place, which price will include furnishing and placing the required bar dowels, all excavation, backfilling, drainage openings, and the satisfactory disposal of all unsuitable and surplus materials. Depressed curb will be considered, and paid for, as standard curb.

(b) Forms.....Metal forms shall be of approved section and shall have a flat surface on top and wooden forms shall be nominal 2" surfaced planks.....Steel templates 1/8 of an inch in thickness, of the width of the curb and not less than 2" longer than the depth of the curb shall be used to separate adjacent sections.

(e) Joints and Reinforcement.....Premolded expansion joints.....at intervals of not more than 93 feet.....At all curb joints or when curved curb joins with tangent curb, at curb returns and on sharp curves two (2) reinforcement bars, #4 size and 24" in length, shall be embedded in the concrete. These bars shall be placed 3" and 12", respectively, below the top of the curb and in the center of its width, and shall extend twelve (12") inches into the curb on each side of the joint.

(f) Removal of Forms: The forms shall not be removed within twelve (12) hours after the concrete has been placed.

(g) Curing: The curb shall be protected and cured as specified in Section 1001.3 (p) P.D.H. Spec. 408-70, except membrane curing will be permitted.


Section 2. All other provisions of Ordinance No. 191 are hereby reenacted and shall remain in full force and effect.

Section 3. Any ordinance or part of an ordinance conflicting with this ordinance is hereby repealed insofar as the same affects this ordinance.

Section 4. If any sentence, clause, section or part of this ordinance is for any reason found to be unconstitutional, illegal or invalid, such unconstitutionality, illegality or invalidity shall not affect or impair any of the remaining provisions, sentences, clauses, sections or parts of this ordinance. It is hereby declared as the intent of the Borough Council and the Mayor of the Borough of Orwigsburg that this ordinance would have been adopted had such unconstitutional, illegal or invalid sentence, clause, section or part thereof not been included therein.

ENACTED and ORDAINED into an ordinance this 9 day of May, A. D., 1973, by the Council of The Borough of Orwigsburg, Schuylkill County, Pennsylvania, in lawful session duly assembled.

BOROUGH OF ORWIGSBURG  
Schuylkill County, Pennsylvania

By:   
President of Council

Attest:

Ernie L. Brown  
Secretary

EXAMINED and APPROVED: This 9 day of May,

A. D., 1973.

James J. Orwig  
MAYOR of the Borough of Orwigsburg  
Schuylkill County, Pennsylvania